



The Guest Room Essential



Vivo 656IP(1D) WiFi Wireless Guest Room VoIP Telephone

Specification

- Maximum of 3 VoIP accounts
- 128 x 64 dot matrix 3" LCD with backlight
- Wideband G.722 Codec
- IPv4/IPv6
- 802.11n/g/b WiFi standard
- Can serve as WiFi AP/WiFi Client/WiFi repeater
- WAN port for wired network connection
- Lan port for PC connection

Server Compliance

- Asterisk/Broadsoft/Alcatel/NEC/Avaya basic features supported

Call Features

- Call Hold
- Call Flash
- Call Waiting Indication
- Last Number Redial. Volatile/In-volatile configurable in Web Portal
- Do Not Disturb (DND)
- Mute



Physical Features

- Four soft keys
- Eight function keys, including one programmable memory button
- LED for MWI
- Power adapter: AC 100 ~ 240V input DC 12V/1.2A output (this option must be specified at the time of order placement)

Wireless Connectivity

- Max bandwidth (802.11n): 150Mbps
- Max bandwidth (802.11g): 54Mbps
- Max bandwidth (802.11b): 11Mbps
- Average effective range (indoors): 20 metres
- Average Transmission Power: 12.5dBm
- WiFi Security Standards: WPA-PSK/WPA2-PSK, WPA, WPA2, 128-bit WEP

Codecs and Voice Features

- Wideband codec: G.722
- Narrowband codec: G.711 μ /A, ILBC
- G.729
- VAD, CNG, AEC, PLC, AJB, AGC
- Full-duplex speakerphone with AEC